

Overview

Upon getting your F110/UX10/T800 tablet you will need to work with your IT group to image the device for use on network. When imaging a device with built-in scanner, DO NOT remove the **Barcode Manager** software as it is to be used for scanning.

Ensure the following prior to use with DPAS

- DoD Root Certs are installed
- CAC reader and software are functioning
- Configure Barcode Manager to DPAS settings

How to Configure Barcode Manager to DPAS Settings

1. Open Barcode Manager
2. On the Control tab
 - a. Under Advanced, make sure 'command mode' and 'single trigger button' are not selected
 - b. Under Advanced > Mode Switch, make sure 'HID keyboard' is selected
3. On the DecoderSetting tab
 - a. Select 'Default'
 - b. Ensure the following Symbologies are enabled: Code 39, Code 128 and PDF417
4. On the Output tab
 - a. Ensure Prefix has no value
 - b. Ensure Suffix has the following value `\r\n`
 - c. Codepage should be set to US-ASCII
 - d. Output Window should have Enable checked and 'Active Window' selected

To test that the tablet is configured, open Notepad on your device and scan a 1D/2D barcode label

The data should be displayed and the cursor should move to the next line when scanning is complete

You are now ready for use with DPAS!

Please see <https://dpasupport.golearnportal.org/index.php/support/software-hardware/handhelds-accessories> for supported hardware information